

A

SERIES

Introducing
the GAME-CHANGER in IC
to Electric Conversions



A 70/600 X
A 80/600 X
A 80/900 X
A 80/1100 X
A 90 X
A 100 X
A 120 X



The **AX series** [A 70/600 X, A 80/600 X, A 80/900 X, A 80/1100 X, A 90, A 100 X, A 120 X] is the ultimate expression of technological research developed by the Carer technical department. It's an eco-friendly, noiseless forklift truck: a good alternative to traditional IC forklifts, contributing to reduce the impact of your work on global warming.

Nominal capacity up to 6000 mm lifting height (side shifter included).

MAIN FEATURES

- **Ideal for outdoor use**
 - front & rear superelastic tires same size
 - excellent ground clearance
- **Excellent performances**
 - travel speed up to 20 km/h and lifting speed up to 0.38-0.50 m/sec
- **Two powerful AC drive motors**
integrated in the front axle to generate acceleration, torque and fast travel speed
- **High autonomy** guaranteed by efficiency and battery up to 96 V - 1720 Ah
- Advanced Multifunctional Display (AMD)
- Luxury seat with automatic weight adjustment
- Automatic parking brake
- Tilting cylinders on the roof
- Proportional reduction of travel speed when cornering
- Lateral battery extraction system
- Rearview camera



A 70/600 X
A 80/600 X
A 80/900 X
A 80/1100 X
A 90 X
A 100 X
A 120 X

Electronics

All truck functions are managed by sophisticated double microprocessor-controlled electronics and regenerative braking. High-efficiency AC traction and pump motors.

Brakes and Energy Regeneration

The oil bath brake system is extremely effective and long lasting.

Energy regeneration can be carried out by braking, releasing the accelerator, reversing the direction and by positive dynamic braking.

The electric brake doesn't depend on the friction between the tires and the ground and ensures a greater contact of the truck to the ground.

Motors

Electric motors are built and tested by CARER with the most advanced technologies.

The AC high efficiency motors perform at high torque, guaranteeing speed, high performances and manoeuvrability. The highly advanced manufacturing technique makes them reliable and durable even under stress.

Two 15 kW traction motors and one 52 kW pump motor work at up to 5400 rpm, providing high torque and high reduction gear.

The motors are IP54 protected against access of dust and water and they allow to optimize power consumption and to guarantee extremely quiet operation.

The new front axle consists of a unique block of two independent units: right and left gear boxes and motors.

Battery

96 V battery, with capacities up to 1680 Ah. The battery is divided two side-by-side boxes and it allows to have easy, safe and fast battery replacement.



Masts

The masts are designed and developed in order to guarantee the highest visibility. They are specifically designed with a superior welded profile, 8 bearings (optional for A 70 X) and an increased wheelbase to suit all applications. The profiles are cold treated to provide optimum resistance to bending and twisting.

The tilting cylinders mounted on the roof structure ensure load stability, high residual capacity and lower torsion to the mast.





A 70/600 X
A 80/600 X
A 80/900 X
A 80/1100 X
A 90 X
A 100 X
A 120 X

Rearview Camera

As standard the machine presents an integrated rearview camera to increase the driver's comfort and safety driving backward.

Operator Compartment

The overhead guard is specifically designed and manufactured using a narrow pillar profile to provide high visibility in all directions.

The forklift is equipped with separate, sealed cabs mounted on silent blocks to provide maximum comfort for the driver, offering a perfect isolation in terms of noiselessness and vibrations. Moreover, the hydraulic pump and front axle gears with helical mechanism ensure maximum silence in all conditions of use.

The operator compartment is spacious and with a generous foot plate. The steering wheel is inclinable and its height adjustable. The comfort seat is heated cushioned full air suspension, with automatic weight adjustment, armrest, backrest extension and safety belt.

Advanced Multifunctional Digital Display

Via an LCD 5.7" advanced multifunctional display, it is possible to adjust the settings of the truck depending on the applications and wishes of the operators to increase the benefits in terms of high performance and comfort. It allows to monitor vehicle speed, driving direction, battery state of charge, drive instantaneous consumption, battery voltage, working hours.

The warning lights show: parking brake, brake failure, no activation of the micro-seat, headlights and direction indicators.

A 70/600 X
A 80/600 X
A 80/900 X
A 80/1100 X
A 90 X
A 100 X
A 120 X



Ergonomics

The optimal driving position offers excellent visibility in all directions. Access to the machines is facilitated by wide non-slip steps and a big handle access. To guarantee the maximum comfort to the driver, the machine has an ergonomic, fabric, heated seat with air suspension and lumbar support (optional for A 70 X)


The armrest is integrated with mini-levers and command buttons. The pedal system can be configured on the specific customer needs: double pedals, directional control at steering wheel or armrest, central brake pedals.

Efficiency

High energy efficiency is ensured by the use of the best market technologies.

The forklift is equipped with two high-speed traction motors with high-reduction gear boxes to provide high productivity.

The electrical system layout has been designed to provide the maximum efficiency and reduce Joule-effect losses. The hydraulic system has been developed using larger sections to decrease the power losses and supplying a significant efficiency increase. The electric valve bank is managed directly by a stepper motor in each section to reduce energy consumption in all the functions and improve the responsiveness.



Optional



A wide range of options allows to tailor the truck to the various operational needs: **fingertip, joystick, heating, air conditioning, radio with remote control, electronic key access, weight indicator system, front camera** and many other accessories enhance the comfort of the driver and help managing information of the vehicle operation from remote.

FEATURES			C.A.R.E.R. Srl							
			A70X	A80X	A80@900X	A80@1100X	A90X	A100X	A120X	
1.1	Manufacturer									
1.2	Manufacturer's type designation									
1.3	Drive		electric	electric	electric	electric	electric	electric	electric	
1.4	Operator type		seat	seat	seat	seat	seat	seat	seat	
1.5	Load capacity/rated load	Q (t)	7	8	8	8	9	10	12	
1.6	Load centre distance	C (mm)	600	600	900	1100	600	600	600	
1.8	Load distance	X (mm)	660 (1) (2)	665 (1) (2)	700 (1) (2)	700 (1) (2)	690 (1) (2)	700 (1) (2)	710 (1) (2)	
1.9	Wheelbase	Y (mm)	2365	2365	2500	2500	2500	2500	2800	
WEIGHTS	2.1	Weight	(kg)	12822	14100	16950	17960	16770	17460	18320
	2.2	Axle loading, laden front / rear	(kg)	17323 / 2499	19469 / 2631	21732 / 3218	23094 / 2866	21980 / 3790	24200 / 3260	27236 / 3084
	2.3	Axle loading, unladen front / rear	(kg)	6590 / 6232	7190 / 6910	8610 / 8340	9174 / 8786	8340 / 8430	9000 / 8460	9620 / 8700
WHEELS	3.1	Tyres type		SE-SEG	SE-SEG	SEG	SEG	SEG	SEG	SEG
	3.2	Tyre size, front		355/50-20 8.25-15	355/50-20 8.25-15	300-15	300-15	300-15	300-15	355/65-15
	3.3	Tyre size, rear		8.25-15	300-15	300-15	300-15	300-15	300-15	300-15
	3.5	Wheels, number front rear (x = driven wheels)		2X/2	2X/2	4X/2	4X/2	4X/2	4X/2	4X/2
3.6	Track width, front	b10 (mm)	1500 1560	1500 1560	1660	1660	1660	1660	1850	
3.7	Track width, rear	b11 (mm)	1450	1450	1450	1450	1450	1450	1440	
DIMENSIONS	4.1	Tilt of mast / fork carriage forward / backward	α/β (°)	6 / 10(2)	6 / 10(2)	6 / 10(2)	6/10(2)	6 / 10(2)	6 / 10(2)	6 / 10(2)
	4.2	Closed mast height	h1 (mm)	2680	2800	2890	2950	2890	2950	2950
	4.3	Free lift	h2 (mm)	100	100	100	100	100	100	100
	4.4	Lift (standard mast)	h3 (mm)	5000	5000	5000	5000	5000	5000	5000
	4.5	Height, mast extended	h4 (mm)	6100	6200	6350	6350	6350	6350	6500
	4.7	Height of overhead guard	h6 (mm)	2895	2895	2895	2895	2895	2895	2895
	4.8	Seat height	h7 (mm)	1700	1700	1700	1700	1700	1700	1700
	4.12	Coupling height	h10 (mm)	820	820	820	820	820	820	820
	4.19	Overall length	L1 (mm)	4715	4715	5490	5890	4880	4890	5190
	4.20	Length to face of forks	L2 (mm)	3515	3515	3690	3690	3680	3690	3990
	4.21	Overall width	b1/b2 (mm)	1860 2000	1860 2000	2200	2200	2200	2200	2500
	4.22	Fork dimensions	exsxL (mm)	150x60x1200	200x60x1200	200x70x1800	200x70x2200	200x60x1200	200x60x1200	200x70x1200
	4.23	Fork carriage iso 2328/30, FEM/A,B		4A	4A	4A	4A	5A	5A	CARER
	4.24	Fork-carriage width	b3 (mm)	1800	1800	2000	2000	2000	2000	2200
	4.31	Ground clearance, laden, below mast	m1 (mm)	200	200	200	200	200	200	200
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	220	220	220	220	220	220	220
4.33	Aisle width for pallets 1000x1200 crossways	Ast (mm)	5065	5065	5250	5250	5240	5250	5910	
4.34	Aisle width for pallets 800x1200 lengthways	Ast (mm)	5265	5265	5450	5450	5440	5450	6110	
4.35	Turning radius	Wa (mm)	3200	3200	3350	3350	3350	3350	4000	
4.36	Internal turning radius	b13 (mm)	1100	1100	1200	1200	1200	1200	1770	
PERFORMANCE	5.1	Travel speed, laden / unladen	(km/h)	19 / 20	19 / 20	19 / 20	19 / 20	19 / 20	17 / 19	15 / 19
	5.2	Lift speed, laden / unladen	(m/s)	0,4 / 0,5	0,4 / 0,47	0,36 / 0,42	0,33 / 0,37	0,33 / 0,33	0,25 / 0,31	0,25 / 0,33
	5.3	Lowering speed, laden / unladen	(m/s)	0,5 / 0,4	0,51 / 0,48	0,57 / 0,43	0,46 / 0,41	0,51 / 0,48	0,4 / 0,34	0,5 / 0,4
	5.5	Drawbar pull, laden / unladen (S2 60')	(N)	8600 / 9600	10700 / 11800	10900 / 12100	10400 / 11500	10400 / 11700	10000 / 11300	7000 / 8800
	5.6	Max. drawbar pull, laden / unladen (S2 5')	(N)	28300 / 29200	30000 / 31000	30400 / 32700	30400 / 31700	30500 / 31700	29500 / 30900	30500 / 32000
	5.7	Gradeability, laden / unladen (S2 30')	(%)	8,5 / 14	8,3 / 14	8,5 / 14	7 / 10,9	7,1 / 11,7	6,4 / 10,9	5 / 9
	5.8	Max. gradeability, laden / unladen (S2 5')	(%)	14,7 / 24,1	14,7 / 23,9	14,2 / 24	12,1 / 18,3	12,2 / 19,3	11 / 18,1	10 / 17,5
	5.9	Acceleration time, laden / unladen (10 m)	(s)	5 / 4,8	4,8 / 4,5	4,6 / 4,6	4,9 / 4,6	4,7 / 4,6	4,9 / 4,6	6,5 / 5
	5.10	Service brake: mech./hydr./electr.		electric	electric	electric	electric	electric	electric	electric
	MOTOR / BATT.	6.1	Drive motor rating (S2 60')	(kW)	2x15	2x15	2x15	2x15	2x15	2x15
6.2		Lift motor rating (S3 20%)	(kW)	52	52	52	52	52	52	52
6.4		Battery voltage	U (V)	96	96	96	96	96	96	96
6.4.1		Rated capacity	K5 (Ah)	1395 / 1475 / 1548	1395 / 1475	1680 / 1720	1680 / 1720	1680 / 1720	1680 / 1720	1680 / 1720
6.5		Battery weight minimum/maximum	(kg)	4000 / 4300	4000 / 4300	4300 / 4500	4300 / 4500	4300 / 4500	4300 / 4500	4300 / 4500
OTHERS	8.1	Type of drive control		inverter	inverter	inverter	inverter	inverter	inverter	inverter
	8.2	Operating pressure for attachments	(bar)	250	250	250	250	250	250	250
	8.4	Sound level at the driver's ear	(dBA)	72	72	72	72	72	72	72

(1) With side-shift integrated in the mast.

(2) Depending on kind of mast: at lifting height over 5.5 m, tilting has to be limited at 6°/6°.

Wheels tyre legend: SE super elastic - SEG super elastic twins - CHS cushion - PN pneumatic - VLK vulkanol; for tires NO MARKING - OIL RESISTANT, please contact CARER.

The performance data refer to a forklift truck in perfect working condition, with battery weight corresponding to the values given in 6.5.

In accordance with VDI Guideline 2198 this specification sheet provides details of the standard truck only. Non-standard tyres, different masts, optional equipment, etc. may result in different values.

The CARER products and specifications are subject to change without notice.



Electric Forklift Trucks

C.A.R.E.R. Srl

via Copernico 13
48033 Cotignola (RA) Italy

phone +39 0545 1938010

fax +39 0545 908070

www.carerforklift.com

info@carerforklift.com

follow us on  